Technical Specification/ Product Datasheet

Clark-Drain Ltd.,
Station Road,
Yaxley,
Peterborough,
PE7 3EQ.
England.

Specific Product Code/s:	**CD C630H-DSL**
Product Group:	Ductile Iron Manhole Covers
Sub-Category:	C250 Recessed Manhole Covers for use in pavements, driveways and parking areas
Material Grade/s:	Spheroid Graphite Iron Grade EN-GJS-500-7 to BS EN 1563:2011 Temporary Bitumen-based paint coating to BS 3416:1991
Basic Dimensions (mm):	Clear Opening = 600 x 600 Overall Size = 780 x 780 Overall Depth = 128 Frame Depth = 94 Internal Tray Depth = 70
Weight (kgs):	Overall = 74 Cover only = 46
Frame Pressure Bearing Area (N/mm^2):	1.27
Load Rating Classification:	C250 (25 tonnes)

Features:

- Kitemark-certified to BS EN124:1994
- Double-seal design for control of odour egress
- Fitted with locking screws for added security and stability in use
- Integral keyholes (suitable for use with CLKS 553 lifting keys, available separately)
- 70mm internal tray depth to suit 50mm blocks

Date Issued: 04/09/15

Due to our continuous product improvement program features and sizes may be subject to change without notice