



hertalan easy cover

0620
hertalan easy cover
EPDM
Hertalan Rubber Products bv, Industrieweg 16
NL 8263 AD Kampen
07
0620-CPD-44520
EN 13956

Flexible sheet for waterproofing – Plastic and rubber sheets for roof waterproofing –
Definitions and characteristics

Covered application: Gravel ballasted sheets and roof gardens, park decks or similar

Thickness of the material	mm	1.2 / 1.3 / 1.5 / 2.0	
Polymer		EPDM	
Characteristic and test method		Specifications	Value or statement
External fire performance (EN 13501-5)	-	Pass	Pass
Reaction to fire (EN 13501-1)	-	Class	Class E
Water tightness (EN 1928)	-	Pass	Pass
Tensile strength (EN 12311-2B)	N/mm ²	≥ 8,0	MLV
Elongation (EN 12311-2B)	%	≥ 400	MLV
Resistance to impact (EN 12691)	mm	≥ 250	MLV
Tear resistance (EN 12310-2)	N	≥ 25	MLV
Joint peel resistance (EN 12316-2)	N/50mm	≥ 25	MLV
Joint shear resistance (EN 12317-2)	N/50mm	≥ 200	MLV
UV Exposure (EN 1297)	-	Pass	Pass
Foldability at low temperature (EN 495-5)	°C	≤ -70	MLV
Root resistance (EN 13948)	-	Pass	Pass
Resistance to static loading (EN 12730)	kg	≥ 25	MLV
Resistant against dangerous substances		The product does not contain dangerous substances	

MLV: Manufacturer's Limiting Value

Hertalan Rubber Products BV, Industrieweg 16
NL 8263 AD Kampen

Tel: +31 (0)38 339 33 33
Fax: +31 (0)38 339 33 34

E-mail: info@hertalan.com
www.hertalan.com



hertalan is a trademark